

# Care CEUs

## OSHA Safety and Health Standards

### Injury and Illness Prevention Programs

1. 'Processes and procedures are created and implemented to control workplace hazards' falls under which OSHA recommended element?

- A. Hazard Identification and Assessment
  - B. Hazard Prevention and Control
  - C. Education and Training
  - D. Program Evaluation and Improvement
- 

### Top 10 Most Frequently Cited Standards

2. For fiscal year 2011, what was the most frequently cited standard?

- A. Scaffolding
  - B. Respiratory Protection
  - C. Electrical, Wiring Methods
  - D. Machine Guarding
- 

### Fatality, Injury and Illness Information

3. Reports of injury, illness, or fatality must be made orally within \_\_\_\_\_ hours of the employer learning of such incidents.

- A. 4
  - B. 6
  - C. 8
  - D. 12
- 

### Walking-Working Surfaces

4. Every hatchway and chute floor opening must be guarded by a hinged floor opening cover equipped with standard railings that leave only one exposed side or a removable railing with toeboard on not more than two sides and a fixed standard railing with

toeboards on all other exposed sides.

- A. True
  - B. False
- 

5. All scaffolds and their components must be capable of supporting, without failure, at least six times the maximum intended load.

- A. True
  - B. False
- 

## Means of Egress

6. Exit doors serving more than 50 people, or at high-hazard areas, must swing in the direction of exit travel.

- A. True
  - B. False
- 

## Occupational Health and Environmental Controls

7. Where showers are required to be provided, one shower must be provided for every \_\_\_\_\_ employees of each sex.

- A. 2
  - B. 5
  - C. 8
  - D. 10
- 

## Hazardous Materials

8. Acetylene, under no condition must be generated, piped, or utilized at a pressure in excess of \_\_\_\_\_ pounds per square inch.

- A. 8
  - B. 15
  - C. 22
  - D. 30
-

9. For fire protection purposes, not more than 660 gallons of Class IA liquids in containers may be located outside of an inside storage room or storage cabinet in a building or any one fire area of a building.

- A. True
  - B. False
- 

## Hazardous Agents

10. Asbestos exposure must not be in excess of \_\_\_\_\_ fiber per cubic centimeter of air as an 8-hour time-weighted average.

- A. 0.1
  - B. 0.5
  - C. 1.0
  - D. 1.5
- 

11. Which vaccination must be offered to all workers, at no cost, who have a reasonably anticipated exposure to blood or other potentially infectious materials?

- A. Influenza
  - B. DPT
  - C. Hepatitis B
  - D. Hepatitis C
- 

12. Employee exposure to chromium (III) must be limited to an airborne concentration of 5 parts chromium (III) per cubic meter of air as an 8-hour time-weighted average.

- A. True
  - B. False
- 

13. The radiation exposure must not exceed how many Rems per calendar quarter on the hands and forearms or feet and ankles?

- A. 1.25
  - B. 7.5
  - C. 12.4
  - D. 18.75
- 

## Welding, Cutting and Brazing

**14. Oxygen must never be used for ventilation.**

- A. True**
  - B. False**
- 

## **Hazardous Equipment and Machinery**

**15. No hoist must be subjected to a load in excess of \_\_\_\_\_% of its rated load.**

- A. 90**
  - B. 100**
  - C. 125**
  - D. 150**
- 

## **General Electrical Safety**

**16. Unqualified employees and mechanical equipment must be at least \_\_\_\_\_ feet away from overhead power lines.**

- A. 4**
  - B. 10**
  - C. 12**
  - D. 30**
- 

**Copyright © 2024 Care CEUs**

**Visit us at <https://www.careceus.com>**